Materials
For Industry

UL1061

300V Semi-Rigid PVC Hookup Wire

Features

- **UL1061**
- **CSA AWM I A/B**
- **Passes VW-1 and Vertical Wire Flame Test**
- **Fully annealed stranded or solid tinned copper per ASTM standards.**

Applications

For internal wiring of computers and other electronic equipment .

UL1061 300V Semi-Rigid PVC Wire					
Part Number	**Gauge**	**Stranding**	**Outside Diameter**	**Stock Colors**	**Spool Put-Ups/ft**
611016-28XXX	28	7x 36	.035	0-9	1000
611061-26XXX	26	7 x 34	.039	0-9	1000
611061-24XXX	24	7 x 32	.044	0-9	1000
611061-22XXX	22	7 x 30	.050	0-9	1000
611061-20XXX	20	10 x 30	.056	0-9	1000
611061-18XXX	18	16 x 30	.067	0-9	500
611061-16XXX	16	26 x 30	.088	0-9	500

XXX— Standard colors include:

0/BLK, 1/BRN, 2/RED, 3/ORG, 4/YEL, 5/GRN, 6/BLU, 7/VIO, 8/GRY, 9/WHT

Ordering Info: (Type of material) (size) (color)
611061 18 XXX

For striped wire: Add "/" and the striped color, example 611007-24BLK/WHT

Technical Data

Specifications:

Tinned copper conductor
.009" Semi-Rigid polyvinylchloride insulation
Dielectric Strength 300 V/Mil
Temperature range -10ºC to +80ºC

Source Associates, Inc.
(408)970-0128 Fax (408)970-9748
www.source.as e-mail: sales@source.as