



SUMITUBE[®] F4

UL & CSA

FLEXIBLE POLYOLEFIN THIN WALL 2 : 1 Shrink Ratio

UL RECOGNIZED 125° C 150V (VW-1)

TYPICAL FEATURES

- 1) SUMITUBE F4 is a very flexible, thin wall, flame retarded, heat-shrinkable polyolefin tubing that is recognized by Underwriters' Laboratories (UL) Subject 224 as a VW-1 rated material.
- 2) Low temperature recovery benefits the user in more rapid installation, with less potential for damage to component insulation systems. Thin recovered walls save space and weight.
- 3) Shrink temperature is 90°.
- 4) Operating temperature range is -55°C to +125°C.
- 5) SUMITUBE F4 is recommended for all general purpose applications for flame retardant tubing such as insulating, color coding, bundling or environmental protection, especially when space or weight is at a premium.

STANDARD SIZES

SIZE	INSIDE DIAMETER AS SUPPLIED (MIN)		INSIDE DIAMETER AFTER RECOVERY (MAX)		WALL THICKNESS AFTER RECOVERY (NOM)	
	INCH	(MM)	INCH	(MM)	INCH	(MM)
3/64	.046	1.2	.023	0.6	.010	0.25
1/16	.063	1.6	.031	0.8	.010	0.25
3/32	.093	2.4	.046	1.2	.012	0.30
1/8	.125	3.2	.062	1.6	.012	0.30
3/16	.187	4.8	.093	2.4	.012	0.30
1/4	.250	6.4	.125	3.2	.014	0.36
3/8	.375	9.5	.187	4.8	.014	0.36
1/2	.500	12.7	.250	6.4	.014	0.36
3/4	.750	19.1	.375	9.5	.017	0.43
1	1.000	25.4	.500	12.7	.020	0.51
1 1/4	1.250	31.7	0.625	15.9	.020	0.51

Standard colors: Black, White, Red, Yellow
Other colors are available upon request

Standard package: Spooled (S)

How to Order: (Type of material) (Size) (Color) (Packaging)

Example: F4 1/4 Black S

Source Associates, Inc.
(408)970-0128 Fax (408)970-9748
www.source.as e-mail: sales@source.as