



SUMITUBE® I

FLEXIBLE IONOMER 2 : 1 Shrink Ratio

TYPICAL FEATURES

- | | |
|---|--|
| 1) SUMITUBE I is a flexible, extremely tough, non-flame retarded, heat-shrinkable ionomer tubing which is resistant to tearing, scuffing and abrasion
2)
3) Shrink temperature is 110° C.
4) SUMITUBE I is extremely lightweight and has exceptional tensile strength. | 5) Operating temperature range is -55°C to +105° C.
6) SUMITUBE I is recommended for applications requiring very light weight and low profile tubing, combined with exceptional toughness.
7) Low specific gravity combined with thin wall results in very light weight tubing, while maintaining excellent mechanical strength. |
|---|--|

STANDARD SIZES

SIZE	INSIDE DIAMETER AS SUPPLIED (MIN)		INSIDE DIAMETER AFTER RECOVERY (MAX)		WALL THICKNESS AFTER RECOVERY (NOM)	
	INCH	(MM)	INCH	(MM)	INCH	(MM)
1mm	.039	1.00	.020	0.50	.006	0.15
2mm	.079	2.00	.039	1.00	.006	0.15
3mm	.118	3.00	.059	1.50	.006	0.15
4mm	.157	4.00	.079	2.00	.008	0.20
5mm	.197	5.00	.098	2.50	.008	0.20

Standard Colors: Black & Clear
Standard Package: Spools.
How to Order: AVAILABLE BY FACTORY QUOTATION ONLY