



Materials For Industry

MILITARY SPECIFICATION PVC WIRE

Features

- Fully annealed stranded tinned copper per ASTM standards. Also available in solid. Please consult.
- Color Coded .016" PVC insulation thickness.
- Voltage Rating: 1000 Volts.
- Temperature Rating: -55°C to +90°C



Applications

Suitable for internal wiring of electrical and electronic equipment.

MIL-W-76B TYPE MW-C 1000V PVC					
PART NUMBER	GAUGE	STRAND-ING	OUTSIDE DIAMETER	STOCK COLORS	SPOOL SIZE / FT
61MW76B-24XXX	24	7/32	.055	0-9	500
61MW76B-22XXX	22	7/30	.061	0-9	500
61MW76B-20XXX	20	10/30	.069	0-9	500
61MW76B-18XXX	18	16/30	.077	0-9	500
61MW76B-16XXX	16	26/30	.090	0-9	500
61MW76B-14XXX	14	41/30	.103	0-9	250
61MW76B-12XXX	12	65/30	.121	0-9	250

XXX— Standard colors include:

0/BLK, 1/BRN, 2/RED, 3/ORG, 4/YEL, 5/GRN, 6/BLU, 7/VIO, 8/GRY, 9/WHT

For striped wire: Add "/" and the striped color, example 61MW76B-24BLK/WHT

Source Associates, Inc.
 (408)970-0128 Fax (408)970-9748
 www.source.as e-mail: sales@source.as