



TCB-F

Braided Copper Cable

Features

Interconnect
Products

Flat braided tinned copper cables are constructed of woven tinned copper strands into a tubular braid and than rolled flat.

- **Soft annealed tin coated copper**
- **Stranded for excellent pliability**
- **QQ-W-343E**
- **ASTM-B-33 +**
- **Meets QQ-B-575B**

Applications

Point to point ground strap, bondingstraps or connecting moving parts.
Recommended for high current use.

TCB-F Tinned Copper Flat Braid					
PART NUMBER	NOMINAL WIDTH	NOMINAL THICKNESS	CURRENT CAPACITY	SPOOL SIZE / FEET	PRICE PER SPOOL
TCB-F-3/32	.093	.020	11	100	\$15.00
TCB-F-1/8	.125	.020	16	100	\$16.00
TCB-F-3/16	.187	.020	25	100	\$18.60
TCB-F-1/4	.250	.030	32	100	\$27.00
TCB-F-3/8	.375	.030	40	50	\$19.50
TCB-F-1/2	.500	.030	53	50	\$21.10
TCB-F-5/8	.625	.030	62	50	\$26.00
TCB-F-3/4	.750	.040	85	25	\$24.00
TCB-F-1	1.00	.045	85	25	\$24.75

Other stranding and size configurations are also available. Round tubular, oval and silver plated copper may also be supplied upon special request. Larger spool sizes and volume pricing is also available upon request.

Source Associates, Inc.
 (408)970-0128 Fax (408)970-9748
 www.source.as e-mail: sales@source.as