



# UL1015 series

600V PVC Hookup Wire



Materials For Industry

## Features

- UL1015
- CSA Type TEW
- Passes VW-1 Vertical Wire Flame Test

## Applications

Rated 2500V peak for electronic circuits and internal wiring of electronic and electrical equipment.

UL1015 series 600V PVC WIRE					
PART NUMBER	GAUGE	STRANDING	OUTSIDE DIAMETER	STOCK COLORS	SPOOL PUT-UPS/FT
61-1015-24XXX	24	7 x 32	.088	0-9	1000
61-1015-22XXX	22	7 x 30	.093	0-9	1000
61-1015-20XXX	20	10 x 30	.100	0-9	1000
61-1015-18XXX	18	16 X 30	.110	0-9	500
61-1015-16XXX	16	26 X 30	.123	0-9	500
61-1015-14XXX	14	41 X 30	.138	0-9	500
61-1015-12XXX	12	65 X 30	.158	0-9	250
61-1015-10XXX	10	105 X 30	.180	0-9	250
61-1028-8XXX	8	133 x 29	.262	0-9	100
61-1283-6XXX	6	133 x 27	.332	0-9	100

XXX— Standard colors include:

0/BLK, 1/BRN, 2/RED, 3/ORG, 4/YEL, 5/GRN, 6/BLU, 7/VIO, 8/GRY, 9/WHT

Ordering Info: (Type of material) (size) (color)  
611015 18 XXX

For striped wire: Add “/” and the striped color, example 611015-24BLK/WHT

## Technical Data

### Specifications:

Tinned copper conductor  
 Polyvinylchloride insulation  
 Dielectric Strength 600 V/Mil  
 Flammability VW-1  
 Temperature range -10°C to +105°C

Source Associates, Inc.  
 (408)970-0128 Fax (408)970-9748  
 www.source.as e-mail: sales@source.as